



### Main

|                               |                       |
|-------------------------------|-----------------------|
| Range of product              | OsiSense XC           |
| Product or component type     | Pre-cabled connection |
| Component name                | ZCMC                  |
| Associated body               | ZCMD21                |
| Number of poles               | 2                     |
| Contacts type and composition | 1 NC + 1 NO           |
| Contacts operation            | Snap action           |

### Complementary

|                          |        |
|--------------------------|--------|
| Product compatibility    | XCMD21 |
| Electrical connection    | Cable  |
| Cable length             | 5 m    |
| Wire insulation material | PvR    |

### Environment

#### Offer Sustainability

|                                  |   |
|----------------------------------|---|
| Sustainable offer status         | Green Premium product   |
| RoHS                             | Compliant - since 0937 - Schneider Electric declaration of conformity |
| Product environmental profile    | Available   |
| Product end of life instructions | Available   |

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.