



Part Number: 3079A

ISA/SP-50 PROFIBUS DP, (1 pr) 22 AWG Solid BC, FRFPE/PVC, Foil+TC
Braid Shld, CMG, PLTC

Product Description

One 22 AWG pair solid bare copper conductors, flame retardant foam polyethylene (FRFPE) insulation, overall Beldfoil® shield (100% coverage) plus a tinned copper braid shield (65% coverage), sunlight resistant PVC jacket.

Technical Specifications

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	Nominal Diameter	No. of Pairs
22	Solid	BC - Bare Copper	0.026 in	1

Total Number of Conductors:	2
-----------------------------	---

Insulation

Material
FRFPE - Flame Retardant Foam Polyethylene

Color Chart

Number	Color
1	Red & Green

Outer Shield Material

Type	Layer	Material	Material Trade Name	Coverage [%]
Tape	1	Aluminum Foil-Polyester Tape	Beldfoil®	100 %
Braid	2	TC - Tinned Copper		65 %

Outer Jacket Material

Material	Nominal Diameter
PVC - Polyvinyl Chloride	0.315 in

Electrical Characteristics

Capacitance

Nom. Mutual Capacitance
8.5 pF/ft

Construction and Dimensions

Stranding

Lay Length
2.75 in

Conductor DCR

Individual Pair Nominal Shield DCR	Nominal Conductor DCR
3.9 Ohm/1000ft	16 Ohm/1000ft

Impedance

Nominal Characteristic Impedance
150 Ohms

High Frequency (Nominal/Typical)

Frequency [MHz]	Nom. Insertion Loss
0.2 MHz	0.27 dB/100ft
4 MHz	0.67 dB/100ft
16 MHz	1.37 dB/100ft

Delay

Nominal Velocity of Propagation (VP) [%]
78 %

High Freq

Frequency [MHz]	Max. Insertion Loss (Attenuation)
0.2 MHz	1.1 dB/100m
4 MHz	2.65 dB/100m
16 MHz	5.4 dB/100m
0.2 MHz	
4 MHz	
16 MHz	

Current

Element	Max. Recommended Current [A]
Per Conductor	2.3 Amps

Inductance

Nominal Inductance
0.282 μ H/ft

Voltage

UL Voltage Rating
300 V RMS (NEC Type CMG)
600 V RMS (UL AWM Style 20201)
300V RMS (NEC Type PLTC)

Applicable Standards & Environmental Programs

CEC/C(UL) Specification:	CMG
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
CPR Euroclass:	Eca
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

Standards

NEC/(UL) Specification:	CMG, PLTC
UL AWM Style:	UL Style 20201 (600 V 75°C)

Flame Test

CSA Flammability:	FT4
IEEE Flammability:	1202

UL Flammability:	UL1685 FT4 Loading
------------------	--------------------

Safety

UL Voltage Rating:	300 V RMS (NEC Type CMG)
--------------------	--------------------------

Suitability

Suitability - Sunlight Resistance:	Yes
------------------------------------	-----

Mechanical Characteristics

Operating Temp Range:	-30°C To +75°C
Bulk Cable Weight:	52(lbs/1000ft)
Max Recommended Pulling Tension:	50(lbs)
Min Bend Radius/Minor Axis:	3.2(in)

Temperature Range

UL Temp Rating:	60°C
-----------------	------

Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

History

Variants

Item #	Color
3079A 0601000	CHROME
3079A 0602000	CHROME
3079A 0603600	CHROME
3079A 0071000	VIOLET
3079A 0072000	VIOLET
3079A 0073600	VIOLET
3079A 0075000	VIOLET

© 2017 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS(Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.