

# BNC Video Noise Filter

Art. no. TVAC25210

Page 1 of 1



- Prevents interference caused by differences in potential
- Ensures earth decoupling between camera and recorder
- Installation of video signal wire between camera and recorder
- Easy and tool-free installation due to BNC plug connections
- Compatible with HD-TVI, HD-CVI, ADH and CVBS Cameras up to 2 MPx (1080p)

Interference-free images for analogue video surveillance In analogue video systems, the BNC interference filter can assist with almost all image interference caused by differences in earth potential. The filter effectively prevents interference like banding, as well as double or shifted images. If it is difficult to carry out an error analysis in previously installed analogue HD systems, the BNC interference filter can be a good solution that provides a fluid and sharp image. Easy installation The filter can be installed between video camera and recorder with a BNC plug connection.

## Technical Data:

Dimensions	40 x 25 x 22 mm
Connectible devices	HD-TVI, HD-CVI, ADH and CVBS Cameras up to 2 MPx (1080p)
Connection type	BNC
Width	40 mm
Height	25 mm
Length	22 mm
Max. operating temperature	55 °C

Max. humidity	95 %
Min. operating temperature	-10 °C
Net weight	0,051 kg
Video output	1
Video input	1
Video input impedance	75 Ω