

tesa® 50577 All Black Aluminium

tesa® 50577 is a strong aluminium tape, based on a black 50µm aluminium foil and a black acrylic adhesive. tesa® 50577 is mainly used in the arts and entertainment industry and in appliance industry as well a wide range of other applications.

Features:

- perfect matt surface and a black adhesive
- good adhesion
- easy to remove without residues
- high temperature resistance
- mechanical resistance
- moisture resistant
- vapour tight
- oil & acid resistant
- ageing-resistant
- available with liner (PV1)

Main Application

- Bonding of coils for heaters, air conditioning systems
- Preventing light escaping from floor cans
- Fixation of forming of barndoors
- High temperatures applications when a removability afterwards is needed
- Invisible repairs with a matt black surface

Technical Data

▪ Backing material	aluminium foil	▪ Tensile strength	40 N/cm
▪ Total thickness	85 µm	▪ Temperature resistance min.	-40 °C
▪ Type of adhesive	acrylic	▪ Temperature resistance max.	160 °C
▪ Adhesion to steel	5 N/cm	▪ Temperature resistance (30 min)	160 °C
▪ Elongation at break	5 %	▪ Surface finish	matt

Properties

▪ Hand tearability	●●●●	▪ Suitable for die cutting	yes
▪ Straight tear edges	●●	▪ Abrasion resistance	●●●●
▪ Easy to remove	yes	▪ Water resistance	●●●●

Evaluation across relevant tesa® assortment: ●●●● very good ●●● good ●● medium ● low

For latest information on this product please visit <http://l.tesa.com/?ip=50577>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.