

## Assembly adapters - UWA 182/52 - 2938235

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Universal wall adapter for securely mounting the device in the event of strong vibrations. The device is screwed directly onto the mounting surface. The universal wall adapter is attached on the top/bottom.

### Product Description

Material: Steel 2.5 mm (St 1203), dimensions: Width 52 mm, height 182 mm, to assemble following power supplies directly on the panel: - QUINT-PS..., QUINT-DC-UPS... und QUINT BUFFER..., TRIO-PS/1AC/ 10+20A, TRIO-PS/3AC/...

### Key Commercial Data

Packing unit	1 pc
GTIN	 4 046356 051156
GTIN	4046356051156
Weight per Piece (excluding packing)	0.208 kg
Custom tariff number	73269098
Country of origin	Germany

### Technical data

#### Dimensions

Width	52 mm
Height	182 mm
Depth	9 mm

#### General

Mounting type	DIN rail mounting
Housing material	Steel, powder-coated

### Classifications

eCl@ss

eCl@ss 4.0	27040702
------------	----------

## Assembly adapters - UWA 182/52 - 2938235

### Classifications

#### eCl@ss

eCl@ss 4.1	27040702
eCl@ss 5.0	27049090
eCl@ss 5.1	34174000
eCl@ss 6.0	27049000
eCl@ss 7.0	27049090
eCl@ss 8.0	27370419
eCl@ss 9.0	27370419

#### ETIM

ETIM 2.0	EC001039
ETIM 3.0	EC001039
ETIM 4.0	EC002625
ETIM 5.0	EC002625
ETIM 6.0	EC002625
ETIM 7.0	EC002625

#### UNSPSC

UNSPSC 6.01	30211502
UNSPSC 7.0901	39121004
UNSPSC 11	39121004
UNSPSC 12.01	39121004
UNSPSC 13.2	39121004